

~~6.~~ (New) A method for ensuring the operation of signaling channels in a V5

interface between a local exchange and an access node, the interface comprising:

reconfiguring V5 interface data in an interface composition having at least two signaling channels; and

ensuring active operation of protected signaling channels when starting a V5 interface, wherein the protected signaling channels are started on signaling channels defined in a new interface composition, and on signaling channels to which the protected signaling channels were transferred in a protection switch-over.

C ~~2.~~ (New) The method as defined in claim ~~1.~~¹, wherein the reconfiguring V5 interface data in the interface composition is carried out independently both in a local exchange and in an access node without changing a value of an interface composition parameter.

C ~~3.~~ (New) The method as defined in claim ~~1.~~¹, wherein the protected signaling channels transferred to a backup channel in a protection switch-over, remain at locations to which they were transferred in the protection switch-over, regardless of the reconfigured composition of the V5 interface.

C ~~4.~~ (New) The method as defined in claim ~~1.~~¹, wherein composition changes in the reconfiguration of the composition of the V5 interface are made in an original composition regardless of protection switch-over operations carried out in the V5 interface.

10

B

C
5
~~10.~~

1
~~6~~
1

(New) The method as defined in claim 1, wherein an interface composition parameter is a provision variant parameter of the V5 interface, wherein the provision variant parameter includes the reconfigured V5 interface data.

11

B